



Paxton

Net2 PaxLock US



Net2 PaxLock is a battery powered Net2 access control unit in a secure door handle and comes ready to install with a C Keyway lock or alternatively to fit with an SFIC lock.

Communication between Net2 PaxLock and the Net2 server is done wirelessly through Net2Air and the Net2Air Ethernet bridges, providing all the advantages of a wireless access control system.

Net2 PaxLock is simple to use and fast to fit because it has a self-contained power source, making it ideal for internal doors.

- Online, wireless, battery powered Net2 access control
- Secure, simple door handle solution that can be fitted in minutes
- Events are reported back to the Net2 server in real time
- Full battery management system with low battery alerts and easy-change AA batteries
- Compatible with EM and Paxton proximity tokens
- Key override option
- C Keyway or SFIC lock case variants
- Two handle designs available - Eclipse and Galaxy

Box Contents

- US Paxlock - Battery slide key
- US Paxlock - Plastic Fitting Kit Washer
- Packaging - Foam insert top layer for US Paxlock
- Packaging - Foam insert middle layer for US Paxlock
- Packaging - Foam insert bottom layer for US Paxlock
- Battery - pack of 4 AA alkaline 1.5V cells
- Fasteners - M4 x 8mm pozi csk machine screw BZP
- Fitting kit - US PaxLock
- Packaging - box OD 252 x 252 x 174mm
- Label - product serial number label 27x10mm
- Label - Tech support international
- Label - Void if seal is broken, 80x30mm
- Battery warning label 30x20mm PaxLock US
- Sales Code label 30x20mm PaxLock US lockset label

Specifications - Net2 PaxLock US C Keyway - Galaxy

System Specification	min	typ	max	units
Maximum total users/tokens			50000	
Token compatibility		125k/Hz Paxton		
Handsfree compatible		Yes		
Door open time	1		60	sec
Silent operation		Yes		
Electrical				
Battery type		4 x AA		
Battery life	20000		30000	operations
Communication				
TCP/IP connection		No		
Wireless		2.4GHz (IEEE 802.15.4)		
RS485		No		
Max no. of ACUs per wireless bridge			10	
Optimum wireless range			50	Feet
Encryption		AES 128bit		
Features				
Door widths supported		2		Inches
Door contact input		Yes		
Rear handle exit request		Yes		
Low battery warning		Yes		
Flat battery jumpstart terminals		No		
Lock case compatibility				
Backset		2.75		Inches
Handle rotation			70	degrees
Lockset		Cylindrical lockset		
Escape function		Refer to Paxton support		
Environment				
Operating temperature	32		131	°F
Moisture resistance		No		
Vandal resistance		Low		
Fire resistance		ANSI/UL 10C, CAN/ULC S104		

- Sales Code label, 40x25mm, UL
- Screw - M4 x 8 phillips pan head
- Drilling Template - PaxLock US
- Bubble pouches - antistatic
- US Paxlock - Secure Side Assy.
- US PaxLock - Backplate, secure side
- US PaxLock - Backplate, insecure side
- Lockset assembly, C-Keyway w Galaxy
- US Paxlock - Insecure Side top level assy

Order #	Item #	List Price
652-5500	PAX 921-430-US PAXLOCK US	\$500. ⁰⁰



Four Convenient Locations

Main Florida Warehouse: 800.282.2837, Fax: 800.447.2299, PO Box 1980, Pinellas Park, FL 33780

South Florida: 888.780.6071, Fax: 954.943.4211, 1445 SW 6th Ct., Pompano Bch, FL 33069 (Se Habla Espanol)

Atlanta: 877.217.9396, Fax: 770.455.3969, 3627 Clearview Pkwy., Doraville, GA 30340

Charlotte: 888.571.9145, Fax: 704.527.0058, 8200-C Arrowridge Blvd, Charlotte, NC 28273

SouthernLock.com

sales@SouthernLock.com



[Facebook.com/SoLock](https://www.facebook.com/SoLock)